

5 **WHAT IS CLAIMED:**

1. For a factory process comprising a plurality of tasks, a method to permit monitoring of the process, the method comprising:
displaying the factory process in real-time as a three-dimensional, free-camera, computer generated representation of the process as a whole; and
10 selectively displaying each of the tasks in real-time as a three-dimensional, free-camera, computer generated representation of the respective task.
- 15 2. The method of claim 1 including selectively displaying data representative of a status of the displayed process.
3. The method of claim 1 including selectively displaying data representative of a status of one of the displayed tasks.
- 20 4. The method of claim 1 including selectively displaying data representative of a status a plurality of the displayed tasks.
5. The method of claim 1 wherein the process has a controllable parameter and the method includes controlling the parameter of the factory process.
- 25 6. The method of claim 1 wherein one of the tasks has a controllable parameter and the method includes controlling the controllable parameter of the task.
7. The method of claim 1 wherein a plurality of the tasks have a controllable parameter and the method includes selectively controlling the controllable parameter of each of the tasks.
30

- 5 8. The method of claim 1 wherein one of the tasks has a sub-task and the method includes selectively displaying the sub-task in real-time as a three-dimensional, free-camera, computer generated representation of the respective task.
- 10 9. The method of claim 8 wherein the sub-task has a controllable parameter and the method includes controlling the controllable parameter of the sub-task.
- 15 10. The method of claim 1 wherein a plurality of the tasks has a respective plurality of sub-tasks and the method includes selectively displaying the sub-tasks in real-time as a three-dimensional, free-camera, computer generated representation of the respective sub-tasks.
- 20 11. The method of claim 10 wherein each of the sub-tasks has a controllable parameter and the method includes controlling the controllable parameter of the sub-tasks.
- 25 12. The method of claim 1 including:
sensing a status of one of the tasks;
determining if the sensed status is acceptable; and
automatically displaying the task if the sensed status is not acceptable.
- 30 13. The method of claim 1 including:
sensing a status of a plurality of the tasks; and
determining if the sensed status of each of the plurality of tasks is acceptable; and
automatically displaying one of the plurality of tasks if the sensed status of the one of the plurality of tasks is determined not to be acceptable.
14. For a factory process comprising a plurality of tasks, a method to permit monitoring of the process, the method comprising:

5 displaying the factory process in real-time as a three-dimensional, free-camera,
computer generated representation of the process as a whole;
 selecting one of the tasks; and
 displaying data representative of a status of the selected one of the displayed
tasks.

10 15. The method of claim 14 including displaying data representative of a status of a
plurality of the displayed tasks.

15 16. The method of claim 14 wherein the process has a controllable parameter and the
method includes controlling the parameter of the factory process.

20 17. The method of claim 14 wherein the one of the displayed tasks has a controllable
parameter and the method includes controlling the controllable parameter of the
task.

25 18. The method of claim 14 wherein the plurality of tasks has a controllable
parameter and the method includes controlling the controllable parameter of each
of the tasks.

30 19. The method of claim 14 wherein one of the tasks has a sub-task and the method
includes selectively displaying the sub-task in real-time as a three-dimensional,
free-camera, computer generated representation of the respective task.

 20. The method of claim 19 wherein the sub-task has a controllable parameter and the
method includes controlling the controllable parameter of the sub-task.

 21. The method of claim 14 wherein a plurality of the tasks has a respective plurality
of sub-tasks and the method includes selectively displaying the sub-tasks in real-

5 time as a three-dimensional, free-camera, computer generated representation of the respective sub-tasks.

22. The method of claim 21 wherein each of the sub-tasks has a controllable parameter and the method includes controlling the controllable parameter of the sub-tasks.

23. For a factory process comprising a plurality of tasks, a computer readable medium containing program instructions for execution by a processor to cause the processor to perform steps to permit monitoring of the process on a video display, the method comprising:

15 displaying the factory process in real-time as a three-dimensional, free-camera, computer generated representation of the process as a whole; and

selectively displaying each of the tasks in real-time as a three-dimensional, free-camera, computer generated representation of the respective task.

24. The method of claim 23 including selectively displaying data representative of a status of the displayed process.

25. The method of claim 23 including selectively displaying data representative of a status of one of the displayed tasks.

26. The method of claim 23 including selectively displaying data representative of a status a plurality of the displayed tasks.

27. The method of claim 23 wherein the process has a controllable parameter and the method includes controlling the parameter of the factory process.

28. The method of claim 23 wherein one of the tasks has a controllable parameter and the method includes controlling the controllable parameter of the task.

5

29. The method of claim 23 wherein a plurality of the tasks have a controllable parameter and the method includes selectively controlling the controllable parameter of each of the tasks.

10

30. The method of claim 23 wherein one of the tasks has a sub-task and the method includes selectively displaying the sub-task in real-time as a three-dimensional, free-camera, computer generated representation of the respective task.

15

31. The method of claim 30 wherein the sub-task has a controllable parameter and the method includes controlling the controllable parameter of the sub-task.

20

32. The method of claim 23 wherein a plurality of the tasks has a respective plurality of sub-tasks and the method includes selectively displaying the sub-tasks in real-time as a three-dimensional, free-camera, computer generated representation of the respective sub-tasks.

25

33. The method of claim 32 wherein each of the sub-tasks has a controllable parameter and the method includes controlling the controllable parameter of the sub-tasks.

30

34. The method of claim 23 including:
sensing a status of one of the tasks;
determining if the sensed status is acceptable; and
automatically displaying the task if the sensed status is not acceptable.

35. The method of claim 23 including:
sensing a status of a plurality of the tasks; and
determining if the sensed status of each of the plurality of tasks is acceptable; and

5 automatically displaying one of the plurality of tasks if the sensed status of the
one is determined not to be acceptable.

36. A system for monitoring a factory process, the factory process comprising a
plurality of tasks, a system comprising:

10 means for displaying the factory process in real-time as a three-dimensional, free-
camera, computer generated representation of the process as a whole; and

 means for selectively displaying each of the tasks in real-time as a three-
dimensional, free-camera, computer generated representation of the respective task.

15 37. The system of claim 36 including means for selectively displaying data
representative of a status of the displayed process.

38. The system of claim 36 including means for selectively displaying data
representative of a status of one of the displayed tasks.

20 39. The system of claim 36 including means for selectively displaying data
representative of a status a plurality of the displayed tasks.

40. The system of claim 36 wherein the process has a controllable parameter and the
25 system includes means for controlling the parameter of the factory process.

41. The system of claim 36 wherein one of the tasks has a controllable parameter and
the system includes means for controlling the controllable parameter of the task.

30 42. The system of claim 36 wherein a plurality of the tasks have a controllable
parameter and the system includes means for selectively controlling the
controllable parameter of each of the tasks.

- 5 43. The system of claim 36 wherein one of the tasks has a sub-task and the system includes means for selectively displaying the sub-task in real-time as a three-dimensional, free-camera, computer generated representation of the respective task.
- 10 44. The system of claim 43 wherein the sub-task has a controllable parameter and the system includes means for controlling the controllable parameter of the sub-task.
- 15 45. The system of claim 36 wherein a plurality of the tasks has a respective plurality of sub-tasks and the system includes means for selectively displaying the sub-tasks in real-time as a three-dimensional, free-camera, computer generated representation of the respective sub-tasks.
- 20 46. The system of claim 45 wherein each of the sub-tasks has a controllable parameter and the system includes means for controlling the controllable parameter of the sub-tasks.
- 25 47. The system of claim 36 including:
means for sensing a status of one of the tasks;
means for determining if the sensed status is acceptable; and
means for automatically displaying the task if the sensed status is not acceptable.
- 30 48. The system of claim 36 including:
means for sensing a status of a plurality of the tasks; and
means for determining if the sensed status of each of the plurality of tasks is acceptable; and
means for automatically displaying one of the plurality of tasks if the sensed status of the one is determined not to be acceptable.

- 5 49. For a factory process comprising a plurality of tasks, wherein both the factory
process and the tasks include controllable parameters, a method to permit
monitoring and control of the process, the method comprising:
displaying the factory process in real-time as a three-dimensional, free-camera,
computer generated representation of the process as a whole;
10 selectively displaying data representative of a status of the displayed process;
selectively controlling the factory process parameter;
selectively displaying each of the tasks in real-time as a three-dimensional, free-
camera, computer generated representation of the respective task;
selectively displaying data representative of a status a plurality of the displayed
15 tasks; and
selectively controlling the controllable parameter of each of the tasks
50. The method of claim 49 wherein one of the tasks has a sub-task and the method
includes selectively displaying the sub-task in real-time as a three-dimensional,
20 free-camera, computer generated representation of the respective task.
51. The method of claim 50 wherein the sub-task has a controllable parameter and the
method includes controlling the controllable parameter of the sub-task.
- 25 52. The method of claim 50 wherein a plurality of the tasks has a respective plurality
of sub-tasks and the method includes selectively displaying the sub-tasks in real-
time as a three-dimensional, free-camera, computer generated representation of
the respective sub-tasks.
- 30 53. The method of claim 52 wherein each of the sub-tasks has a controllable
parameter and the method includes controlling the controllable parameter of the
sub-tasks.
54. The method of claim 50 including:

5 sensing a status of one of the tasks;
determining if the sensed status is acceptable; and
automatically displaying the task if the sensed status is not acceptable.

55. The method of claim 50 including:

10 sensing a status of a plurality of the tasks; and
determining if the sensed status of each of the plurality of tasks is acceptable; and
automatically displaying one of the plurality of tasks if the sensed status of the
one is determined not to be acceptable.

15